



America


CERTIFICATE

No. U8 16 08 13563 130

Holder of Certificate: **Arnold & Richter Cine Technik GmbH & Co Betriebs KG**

Pulvermühle
83071 Stephanskirchen
GERMANY

Certification Mark:



Product: **LED Luminaires**
LED luminaires for professional use

The product was voluntarily tested according to the relevant safety requirements noted above. It can be marked with the certification mark above. The mark must not be altered in anyway. This product certification system operated by TÜV SÜD America Inc. most closely resembles system 3 as defined in ISO/IEC 17067. Certification is based on the TÜV SÜD "Testing and Certification Regulations". TÜV SÜD America Inc. is an OSHA recognized NRTL and a Standards Council of Canada accredited certification body.

Test report no.: 028-713087284-000

Date, 2016-09-06

Page 1 of 2





America

CERTIFICATE

No. U8 16 08 13563 130

Model(s):

Skypanel S30-X
 Skypanel S30-X TUNEABLE
 Skypanel S60-X
 Skypanel S60-X TUNEABLE
 Skypanel S120-X
 Skypanel S120-X TUNEABLE
 Where X can be any alphanumeric character or a combination of any alphanumeric characters or blank and describes the version of the LED luminaire.
 For example:
 X = C: (Color) - nominal color temperature: 2800 K – 10000 K + RGBW-light
 X = D: (Daylight) - nominal color temperature: 5600 K
 X = RP: (Remote Phosphor) - color temperature selection by changeable remote phosphor panels
 X = T: (Tungsten) - nominal color temperature: 3200 K
 TUNEABLE: color temperature is tuneable in a defined range

Brand Name:

ARRI

Parameters:

Rated power:
 Skypanel S30 versions: max. 200 W (LED)
 Skypanel S60 versions: max. 400 W (LED)
 Skypanel S120 versions: max. 400 W (LED)

Protection class: III

Degree of protection: IP20

Rated voltage: 48 V DC (= Input of electronic control gear)
 or 23 – 36 V DC (= battery input)

Tested according to:

UL 1573:2003
 CAN/CSA C22.2 No. 166-15:2015
 CAN/CSA C22.2 No.9.0S1-97:2011
 UL 8750:2014

Production Facility(ies):

13563