

Mole-Richardson®



5,000 WATT SKYLITE

TYPE 245



FEATURES

Provides a soft and even fill-light for lighting backings or extremely large cyc's in Television, Motion Pictures, and Still Photography. Diffuser Holder and Diffuser Frame are available for using diffusion materials for a softer fill-light. Equipped with Safety Screen.



Type 24515 Diffuser Holder

NEW




Type 24549 Safety Screen

DIFFUSER HOLDER KIT


NEW



* Type 24552 Diffuser Holder
(Includes both Type 24515 Diffuser Holder and Type 24549 Safety Screen in one assembly).



Type 450260
2-Way Barn Door



Type 450267
4-Way Barn Door



Type 450481A
Moledisk Diffuser Frame



Type 450763S Single
Moledura Scrim



Type 5001652
60 Amp Extension Cable
25 Feet



Type 500350 Heavy Duty
C-Clamp and Adapter Assembly



Type G140
Scrim Bag



Type 500305
Trapeze

ACCESSORIES

- 24515 Diffuser Holder (Skirt)
Required for mounting all light control accessories.
- 24549 Safety Screen Kit
Attaches to Type 24515 Diffuser Holder

*24552 Diffuser Holder & Safety Screen Kit
(Includes both Type 24515 Diffuser Holder and Type 24549 Safety Screen in one assembly).

- 450260 2-Way Barn Door (6 Leaf)
- 450267 4-Way Barn Door (8 Leaf)
- 450481A Moledisk Diffuser Frame (29" dia.)
- 450746 Molering Diffuser Frame (29" dia.)
- 450762S Half Single Moledura Scrim—Stainless Steel Screen (29" dia.)
- 450762D Half Double Moledura Scrim—Stainless Steel Screen (29" dia.)
- 450763S Single Moledura Scrim—Stainless Steel Screen (29" dia.)
- 450763D Double Moledura Scrim—Stainless Steel Screen (29" dia.)
- 1921 5kw to 2kw Socket Adapter
- 450840 Scrim Box
- G140 Scrim Bag
- 500305 Trapeze
- 5001652 60 Amp Extension Cable—25 ft.

STAND SUBSTITUTIONS

- 1411 Junior Size Low
- 1561 Junior Size Sky-Hi
- 500476 Junior Size Litewate
- 500557 Junior Size Litewate
Location—less casters
- 500563 Junior Size Litewate
Location—with casters
- 500572 Folding Crank-up Litewate

GLOBE TABLE

TYPE 245 SKYLITE

Base, mogul bipost. Burn within 45° of vertical base-down. T-17, T-20, T-64 and G-64 bulb; 6 1/2" L.C.L.

Watts	Ordering Code	Color Temp.*K	Finish	Volts	Life Hours	Amps
5000	DPY	3200	Clear	120	500	41.6
5000	ECN	3200	Clear	120	150	41.6
5000	EDN	3350	Clear	120	75	41.6

Globes are not included in price of lamp.
See price list for complete details.

SPECIFICATIONS

HEAD: Type 245, 5,000 watts.
RATING: 120/240 volts, A.C. or D.C., 41.6 amps max.—5,000 watts max.
SOCKETS: Mogul Bipost. Spring loaded contacts.
SWITCH: 60 amps, 125 volts heavy-duty double pole, snap action, mounted in rear of socket casting.
CABLE: 3 ft. Type SO, 3 conductor #6 AWG with MC257G 3 pin plug.
CONSTRUCTION: Steel reflector with cast aluminum socket housing and switch cover.
YOKE: Tubular steel and brass castings with removable 1 1/8" dia. steel yoke pin.
REFLECTOR: Steel with white reflecting surface.
SIZE: 27 1/2" diameter by 4 5/8" deep reflector.
FINISH: Maroon Powder Coat Enamel.
HEAD WEIGHT: 22 lbs.
DIFFUSER HOLDER: Accessory Type 24552. Includes Type 24515 Diffuser Frame and Type 24549 Safety Screen.

PERFORMANCE DATA

TYPE 245 SKYLITE

Using DPY, 5,000 watt, 120 volt, 3200°K quartz globe.

Distance Feet	Without Diffuser Holder		With Diffuser Holder	
	Light Intensity F.C.	Beam Diameter* Feet	Light Intensity F.C.	Beam Diameter* Feet
10	500	14.0	580	11.5
15	245	19.7	275	16.8
20	145	25.5	155	22.1
25	95	31.0	105	27.5
30	65	37.2	70	33.0
35	50	43.4	55	38.5
40	35	49.6	40	44.0
45	30	55.8	30	49.5

*Light tapers smoothly at edge of field. Diameters listed define flat areas diameters at which the intensities are approximately 50% of tabulated intensities at beam center.

Mole-Richardson Co.

937 North Sycamore Avenue, Hollywood, California 90038-2384 U.S.A.

Tel. (323) 851-0111 Fax. (323) 851-5593 E-Mail: info@mole.com

World Wide Web: http://www.mole.com

©Mole-Richardson Co., Hollywood, CA



Litho in U.S.A.